# ESCC600-32Q 6.4T 1RU 32 PORTS 200G ETHERNET SWITCH





- 1RU, 19 INCH RACK MOUNTABLE DESIGN
- CHIPSET: INNOVIUM TERALYNX(IVM77510) 6.4T

### FRONT PANEL

- ✤ 32 ports 200G (QSFP56) can configured as 100G (QSFP28)
- Each port can support configurable to 200/100/50/40/25/10G
- 1 OOB/BMC port
- 💠 1 Console
- 💠 1 USB Type A
- System, Diag mode, OOB link, Per PSU connected, Per Port link speed

# REAR PANEL

- 2 hot swappable CPRS 800W Redundant Power Supplies
- 5 hot swappable Redundant FAN Modules

# DEDICATED SLOT FOR CPU BOARD. (COMe TYPE 7)

- Intel Denverton or Broadwell-DE (Optional)
- BMC: Aspeed or Intel IE BMC support
- SO-DIMM w/ECC (4GBx2 option)
- ♦ M.2(NGFF) and mSATA (Reserved)
- Dimension: W440 x D470 x h44mm, weight: 10.6kg
- Operating Temperature: 0~45°C
- Max System Load: ≈640w(with 5W Transceiver per Port)
- Typical Load: ≈330W(DAC)

### Reach us by sales@cameo.com.tw





SPINE

TOR