



CAMEO
Networking Built to Order

CXS-1000 Series



HIGHLIGHT

- 8 10Gigabit ports
 - IEEE 802.3bt PoE++ support per port 90W
 - 280W PoE power budget per device
 - 160 Gbps switching capacity
 - 12 KByte jumbo frame
 - Non-blocking switching architecture for maximum wire-speed performance
 - Store-and-Forward forwarding method
 - Smart fan design
 - Supports IEEE 802.3az Energy Efficient Ethernet
-

PRODUCT SPECIFICATIONS

Hardware Specifications		
Model Name	DXS-108I	DXS-108BI-280
Interfaces		
100/1G/2.5G/5G/10GBASE-T	8	8
PoE Specifications		
PoE Port	-	8
PoE Standard	-	IEEE 802.3bt, 90W
PoE Power Budget	-	280W
Performance		
Switching Capacity	160 Gbps	
MAC Address	16 K	
Buffer Memory	12 Mbit	
Jumbo Frame	12 KByte	
Power		
Input	100 to 240 VAC, 50/60 Hz	
Power Consumption	37.817W	43.78W (PoE Off) 355.37W (PoE On)
Green Feature		
Energy Efficiency Ethernet	Yes	
Physical Specification		
Enclosure Form Factor	Wall Mount	
Material	Metal	
Dimensions (W x D x H)	280 x 180 x 44 mm	330 x 250 x 44 mm
Weight	1.70 Kg	2.66 Kg
Quantity of Fan	1	2
Environmental Specifications		
Operating Temperature	0 ~ 50° C	
Storage Temperature	-20 ~ 70° C	
Operating Humidity	5 ~ 95% RH (non-condensing)	
Storage Humidity	5 ~ 95% RH (non-condensing)	